



HYSUCAT 23 RIGID INFLATABLE

Note: Specifications for the Hysucat 23 RIB are intended to allow a buyer to understand what equipment is included in the base price. Suppliers and vendors change models and sometimes products or equipment specified are not available. Hysucat reserves the right to make necessary substitutions and will work with each client to identify significant changes.

BRIEF SPECIFICATONS
LOA - 22'4" (6.8 m)
GRP length – 19'4" (5.9 m)
Beam - 8'6" (2.6 m)
Draft – 1'2" (0.36 m)
Dry weight (with engines) – 2,090 lbs. (0.95 metric tons)
Tube diameter – 1'7" (0.51 m)
Fuel capacity – 40 gal. (151 litres)
Maximum HP – Twin 90 HP
Minimum HP – Twin 60 HP
Recommended HP – Twin 70 HP
Cruise speed - 30 – 40 Mph (26 – 34 knots)
Maximum speed – 50 Mph (43 knots)
FULL SPECIFICATIONS
100% Hand Laid Vinyl Ester Construction.
Self-draining Deck
'Valmex' Buoyancy Tubes (7 chambers)
Dihedral Stainless Steel Main Hydrofoil
(2) Stainless Steel Stern Foils
Rub Rail
(2) Aluminum Passenger Safety Rails on the Bow
Stainless Steel Bow Eye
(2) Stainless Steel Stern Eyes
(4) Stainless Steel Mooring Cleats
(2) Large Deck Drains
Center Console with Windshield and Storage
Aluminum Bench Seat w/Backrest
Console Recessed Hand Rails
Electronics Area that Accommodates 12" Displays

LED Navigation Lights
LED Cockpit Lights
(2) Battery System with Battery Switches
12 V Plug – USB lug
(2) 12V Automatic Bilge Pumps
(2) 20 Gallon Fuel Tanks Located Under Deck
Aft Aluminum Bench Seat w/Walk Thru
Armstrong RIB Swim Ladder Side Mount
Stainless Steel Propellers with Engines
Bow Anchor Locker with Drain
OPTIONS
Underwater Lights Package
Table/Casting Platform Insert with Cushion
Hull Colors
Tube Colors (1 month additional delay)
Console Matching Color on Sides
Syntec Ultrafoam Decking
Integrated Battery Charging System
Fusion Bluetooth Stereo System w/4 Speakers
T-Top Aluminum Frame w/Fiberglass Top
Danforth Anchor, 200' Rode, & Chain
Fresh Water Washdown w/5 Gallon Tank